

Product Data Sheet

Sentryline-M Wire Rope Barrier

Last Updated: September 2023



| | |
|-----------------------|------------------------------------|
| Containment Level | MASH TL4 |
| Impact Condition | 10,000 kg rigid truck, 90km/h, 15° |
| Dynamic Deflection | 3.02 m |
| Standard Post Spacing | 3.0 m centres |

| | |
|-----------------------|-------------------------------------|
| Containment Level | MASH TL3 |
| Impact Condition | 2270 kg pick-up truck, 100km/h, 25° |
| Dynamic Deflection | 3.02 m |
| Standard Post Spacing | 3.0 m centres |
| Dynamic Deflection | 2.14 m |
| Standard Post Spacing | 2.0 m centres |

| | |
|----------------------|------------------------------------|
| Point of Redirection | 13.5 m from anchor |
| System Mass | 8.2 kg per metre |
| System Finish | Hot dip galvanized & powder coated |

| | |
|-----------------------|--|
| Installation Variants | Base plate installation |
| | Alternate anchor footing block – 3.4L x 1.5W x 0.74D |
| | Alternate anchor footing block – 3.4L x 1.0W x 1.0D |



Product Data Sheet

Sentryline-M Wire Rope Barrier

Sentryline-M Wire Rope Barrier

