

Product Data Sheet

RhinoStop® Heavy Duty



Updated: February 2026



Crash Test Evaluation

Barrier Configuration	Vehicle Type	Vehicle Mass	Impact Speed	Impact Height	Impact Energy
4 m w-beam supported by six (6) posts at 0.8 m centres positioned on the outside edge of a 150 mm elevated concrete slab.		2000 kilograms	30 km/h	0.5m	67.2 kilojoules
6 m w-beam supported by four (4) posts at 2.0 m centres positioned on the outside edge of a 150 mm elevated concrete slab.		2000 kilograms	20 km/h	0.5m	29.6 kilojoules

Installation

Anchor Type	Drill Depth	Torque	Anchors per Post	Minimum Slab Thickness
M20 Fischer FBN II	115 mm	200 Nm	2 off	150 mm

Post Detail



Feature & Benefits

- Crash tested to exceed the 240kN impact condition nominated in AS/NZS 1170.1, Clause 3.8.
- Nil damage to the anchors or 150mm thick elevated slab following crash testing.
- The yielding of the baseplate allows the system to deflect and absorb higher impact loads.
- Fully modular design, can be configured with pedestrian fall protection up to 1300 mm high.
- All steel construction providing long term durability.
- Fewer anchor bolts when compared to traditional rigid post systems.

Product Data Sheet

RhinoStop® Heavy Duty



Updated: February 2026

